

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-257781

(43)Date of publication of application : 19.09.2000

(51)Int.Cl.

F16L 33/23

F16L 19/08

F16L 21/04

(21)Application number : 11-059222

(71)Applicant : KUBOTA CORP

(22)Date of filing : 05.03.1999


(72)Inventor : NAKAMURA RYOICHIRO

## (54) TUBE FITTING FOR SOFT TUBE

### (57)Abstract:

**PROBLEM TO BE SOLVED:** To improve sealing performance and to prevent torsion of a tube.

**SOLUTION:** A fastening ring 26 is arranged in a deep part of a socket 18 and an O ring 30 is arranged on more opening side than it on this tube fitting. Consequently, an outer surface of a tube 12 to be sealed by the O ring 30 is never marred by a biting tooth 32 of the fastening ring 26. Additionally, as a taper ring 28, a pressing ring 38, etc., are interposed between the fastening ring 26 and a box nut 16, the fastening ring 26 locked to the outer surface of the tube 12 following the box nut 16 is never rotated.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]